# ADAM-4510/S ADAM-4520 ADAM-4521

RS-422/485 Repeater

Isolated RS-232 to RS-422/485 Converter

### Addressable RS-422/485 to RS-232 Converter



ADAM-4510/4510S

## **Specifications**

#### General

- Connectors
- 2 x plug-in terminal blocks (#14 ~ 22 AWG) (RS-422/485)

RS-485 (2-wire) or

RS-485 (2-wire) or

1,200, 2,400, 4,800, 9,600,

115.2 k, RTS control and RS-422 (switchable)

19.2 k, 38.4 k, 57.6 k,

RS-422 (4-wire)

RS-422 (4-wire)

- 3,000 V<sub>DC</sub> (ADAM-4510S) Isolation Voltage
- Power Consumption 1.4 W @ 24 V<sub>DC</sub>

#### **Serial Communications**

- Input
- Output
- Speed Modes (bps)

DAM 0 3030030030 ADAM-4520 

## **Specifications**

#### General

- Connectors
- Isolation Voltage
- Power Consumption 1.2 W @ 24 V<sub>DC</sub>

#### Serial Communications

- Input
- Output
- Speed Modes (bps)

RS-485 (2-wire) or RS-422 (4-wire) 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k,

DAM -----........... ADAM-4521

## **Specifications**

#### General

- Connectors
- 1 x plug-in terminal block (#14 ~ 22 AWG) (RS-422/485) 1 x DB9-F (RS-232)
- Isolation Voltage 1,000 V<sub>DC</sub>
- Power Consumption 1.0 W @ 24 V<sub>DC</sub>
- Built-in microprocessor and watchdog timer

#### **Serial Communications**

•	Input	RS-485 (2-wire) or
		RS-422 (4-wire)
•	Output	RS-232 (DB9)
•	Speed Modes (bps)	300, 600, 1,200, 2,400,
		4,800, 9,600, 19.2 k,
		38.4 k, 57.6 k, 115.2 k
		(software configurable)
<ul> <li>RS-232 and 485 can be set to different</li> </ul>		

- baudrates **RS-485** surge protection and automatic RS-485 data flow control
- Software configurable to either addressable or non-addressable mode

### **Common Specifications**

#### General

Power Input

#### **Environment**

Temperature

- Operating Humidity Operating
- 5~95% RH

Unregulated 10 ~ 30 V<sub>DC</sub> w/ power reversal protection

- 10 ~ 70°C (14 ~ 158°F)
- Storage Temperature 25 ~ 85°C (-13 ~ 185°F)

## **Ordering Information**

ADAM-4510 RS-422/485 Repeater **ADAM-4510S** Isolated RS-422/485 Repeater ADAM-4520 Isolated RS-232 to RS-422/485 Converter ADAM-4521 Addressable RS-422/485 to RS-232 Converter

1 x plug-in terminal block (#14 ~ 22 AWG) (RS-422/485) 1 x DB9-F (RS-232) 3,000 V<sub>DC</sub>

RS-422 (switchable)

RS-232 (DB9)

# 115.2 k, RTS control and





# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advantech: ADAM-4510S-EE