

Eaton 276272

Catalog Number: 276272

Main load disconnect Switch with isolation function, highly wear resistant contacts and classified for the use in rail rolling stock, 240/415 V, 40 A, 3P



Foto je reprezentativní

General specifications

Product Name	Catalog Number
Eaton Moeller series IS Disconnect	276272
Packing Unit	EAN
Case Pack	9007912419310
Quantity	Gross Weight
40	13.109 kg
Length	Width
385 mm	180 mm
Height	Volume
230 mm	15.939 dm ³
ERP Name	Product Length/Depth
SAP-UNITY	60 mm
Product Height	Product Width
80 mm	53.1 mm
Product Weight	Compliances
0.305 kg	RoHS conform
Certifications	Model Code
EN45545-2 IEC 61373	IS-40/3

Type

IS. Main load disconnect switch

Application

Switchgear for industrial and advanced commercial applications

Degree of protection

IP40

IP10

Terminals

Lift terminal

Equipment heat dissipation, current-dependent

2.2 W

Imprint/indication

Symbol "arrows"

Lamp socket

Other

Ambient operating temperature - max

40 °C

Ambient operating temperature - min

-5 °C

Built-in depth

69.5 mm

Heat dissipation capacity

0 W

Heat dissipation per pole, current-dependent

1.9 W

Lamp power

0 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

3

Amperage rating

40 A

Color calotte

Other

Certifikáty

DA-DC-03_IS

Schémata zapojení

IS_3P

Výkresy

eaton-dimensions-mas-is.jpg

1221172

Switch type

Other

Rated short-time withstand current (Icw)

1 kA

Voltage type

AC

Lamp type

Other

Number of contacts (normally open contacts)

3

Rated operational current for specified heat dissipation (In)

40 A

Rated operational voltage (Ue) - max

415 V

Rated switching capacity

12.5 kA

Static heat dissipation, non-current-dependent

0 W

Voltage rating - min

240 V

Width in number of modular spacings

3

Number of poles

Three-pole



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. Všechna
práva vyhrazena.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia